



## Manure and Hay Forks

for Wheel Loaders and  
Telescopic Handlers



- The **Dymax Manure and Hay Fork** is the perfect attachment for any feedlot or ranching application.
- The design of the **Dymax Manure and Hay Fork** provides precise and secure operator control of a variety of sizes and conditions of hay, straw and manure.
- The **Manure and Hay Fork** is designed and built for strength and durability, insuring optimum productivity and long life.
- The top clamp features an open design for maximum visibility.
- Available for wheel loaders and telescopic material handlers, a different model is available for skid steer loaders.
- Customized features can be incorporated into the **Dymax Manure and Hay Fork**, including a variety of widths, tine length and tine spacing.

## Manure and Hay Forks



### Specifications

Carriage width (in.)	92
Carriage height (in.)	44 1/2
Top clamp width (in.)	86
Top clamp grapple spacing (in.)	28 1/2
Top clamp opening (in.)	76
# Cylinders	2
Rod (in.)	1 3/8
Stroke (in.)	8
Bore (in.)	2 1/2
# Tines (box design)	9
Tine diameter (in.)	2
Spacing between tines (in.)	11
Tine length (in.)	38
Weight (lbs.)	1,400

Materials and specifications subject to change without notice



402 Miller Drive • P.O. Box 297 • Wamego, Kansas • 66547 • 1-800-530-5407  
[www.DYMAXattachments.com](http://www.DYMAXattachments.com)

Form No. 4551 (2-01)