

DYMAXINC

EXTREME DUTY LOADER ROOT RAKES WITH DOUBLE GRAPPLES
for Wheel Loaders and Track Loaders



www.DYMAXINC.com

DYMAX SPECIALTY ATTACHMENTS

EXTREME DUTY LOADER ROOT RAKES WITH DOUBLE GRAPPLES

Dymax Extreme Duty Loader Root Rakes with Grapples are built to provide years of productive use and are backed by the best service in the industry.

Dymax Extreme Duty Loader Root Rakes feature high tensile steel construction and feature dual top clamps. Each model is fitted with relief and counterbalance valves for smooth performance and long durability.

Dymax Extreme Duty Loader Root Rakes with Grapples are available as direct mount pin-on models, or can be equipped with coupler hooks to fit Dymax coupler systems and other popular systems such as JRB, Volvo or Caterpillar models.

Lower tines are designed using Hardox 400 with a weld on replaceable tooth. Each tooth is manufactured by Dymax and features carbide overlay for improved wear service life.

Each model is provided with stands to assure easy uncoupling from the loader during storage.

SPECIFICATIONS

Model No.	Description	Weight (lbs)	Weight (kgs)
DX-RK-XSDG-108in-WL-50	Rake - Extreme Service Double Grapple - 108 inches wide - Wheel Loader - Class 50 (8 teeth)	6,200	2,812
DX-RK-XSDG-120in-WL-60	Rake - Extreme Service Double Grapple - 120 inches wide - Wheel Loader - Class 60 (10 teeth)	7,000	3,176
DX-RK-XSDG-120in-WL-70	Rake - Extreme Service Double Grapple - 120 inches wide - Wheel Loader - Class 70 (10 teeth)	7,000	3,176
DX-RK-XSDG-135in-WL-80	Rake - Extreme Service Double Grapple - 135 inches wide - Wheel Loader - Class 80 (10 teeth)	8,800	3,991
DX-RK-XSDG-144in-WL-90	Rake - Extreme Service Double Grapple - 144 inches wide - Wheel Loader - Class 90 (12 teeth)	10,000	4,536
DX-RK-XSDG-194in-WL-100	Rake - Extreme Service Double Grapple - 194 inches wide - Wheel Loader - Class 100 (16 teeth)	17,100	7,756

Specifications are subject to change without notice.

FEATURES

- Two heavy duty independent grapples comprised of high strength T1 steels.
- Includes relief and counterbalance valves provide smooth and controlled performance during open and close cycles.
- Includes stand legs for easy uncoupling from loader.
- Available as direct mount pin on model, or can be equipped with coupler hooks.
- Equipped with solid AR400 steel tines fitted with weld on replaceable tine tips.
- AR400 tine tips include carbide overlay for long wear service life.
- Heavy duty long stroke cylinders which yield a wide opening.
- Tine spacing and custom designs are available upon request.
- Available for track and wheel loaders.



DYMAX INC | Toll Free: 800.530.5407 (USA/CAN)
402 Miller Drive | Office: +1.785.456.2081
Wamego, KS 66547 USA | Fax: +1.785.456.8328

www.DYMAXINC.com
sales@DYMAXINC.com