



Dymax QWIKSAWZ

Skid Steer Loaders
Multi-Terrain Loaders



Photo Above: The Dymax Qwiksaw provides superb saw cuts as shown on hedge stump above.

Photo Left: Dymax fixed boom Qwiksaw

- The **Dymax Qwiksaw** is the best engineered, toughest tree saw on the market.
- Backed by the best service and support the **Dymax Qwiksaw** delivers high speed power packed performance that spins whirlwinds around the competition.
- The **Dymax Qwiksaw** is available as a fixed boom or swing boom model. Fixed boom models are available in standard flow or high flow while the swing boom model is only available for high flow machines. *(Hoses to machine lines are sold separately and must be specified.)*
- The **Dymax Qwiksaw** features replaceable bolt on carbide teeth which are guaranteed to stay tight. *(Life of tooth subject to variety of elements inherent with land clearing applications. Life of teeth will vary. Ask your dealer or contact Dymax 1-800-530-5407 to determine which tooth style is best for your application).*
- Approaching 80 years of experience in designing and building the highest quality attachments for land clearing applications. Quality, Integrity, Performance and Service our family tradition since 1930.
- Contact **Dymax 1-800-530-5407** or send us an email sales@dymaxattachments.com All Dymax products are sold through authorized dealers.

The family of
QWIKSAW Tree Saws

For more information
call Dymax Sales 1-800-530-5407



DYMAX FIXED BOOM QWIKSAWZ - SKID STEER LOADERS

Standard Flow Models

- (10) **CARBIDE** teeth are guaranteed to stay tight!
- Heavy duty motor and gear box assembly with self tightening hardware.
- 30" diameter, 1/2" thick high speed cutting disk (1200-1950RPM)
 - Required Flow is 18 to 27 GPM, 3500psi
 - 140 ft. lbs Torque
- Tree pushbar and deflector shield
- Optional sprayer system available - Weight (lbs)1010

High Flow Models

- (12) **CARBIDE** teeth which are guaranteed to stay tight!
- Heavy duty motor and gear box assembly with self tightening hardware.
- 38" diameter, 1/2" thick high speed cutting disk (1200-1750RPM)
 - Required Flow is 28 to 41 GPM, 3500psi
 - 230 ft. lbs Torque
- Tree pushbar and deflector shield
- Optional sprayer system available
- Case drain required -Weight (lbs) 1120



DYMAX HIGH FLOW SWING BOOM QWIKSAW SKID STEER LOADERS

**available only for high flow skid steers*

- (12) **CARBIDE** teeth are guaranteed to stay tight!
- Heavy duty motor and gear box assembly with self tightening hardware.
- 38" diameter, 1/2" thick high speed cutting disk (1200-1750RPM)
 - Required Flow - 28 to 41 GPM, 3500psi
 - 230 ft. lbs Torque
- Tree pushbar and deflector shield
- Optional sprayer system available
- Case drain required.
- Weight (lbs) 1,370

NOW AVAILABLE - ALL NEW COMMERCIAL CUTTER DISK AND BEARING HOUSING.
3/4" THICK DISK, CARBIDE THRU-BOLT CUTTING TEETH
HEAVY DUTY BEARING HOUSING

CUT YOUR CUTTING COSTS WITH A DYMAX QWIKSAW

Materials and specifications subject to change without notice



402 Miller Drive • P.O. Box 297 • Wamego, Kansas • 66547 • 1-800-530-5407
www.DYMAXattachments.com or www.TreeShears.com www.QwikSaw.com

Form No. 7870 (10-08)