



Four motor Ballast Tamper

Hydraulic Excavators



Heavy duty 4
motor tamper shown
in stand assembly



Dymax four (4) motor ballast tampers provide optimum tamping performance for excavators working off-track.

Equipped with four (4) vibratory motors, the Dymax four (4) motor tamper allows tie gangs to tamp larger sections without the need for having on-track equipment.

Features hydraulic rotation and gives operators the ultimate flexibility when it comes to positioning. Diverter valve kits are optional.

Features eight (8) Dymax chrome carbide tamping tools.

Dymax 4 motor tampers are available for all makes and models of excavators. Machines must have at least 30GPM of hydraulic flow.

Contact Dymax sales for more information **1-800-530-5407** or your local Dymaxrail equipment dealer.



SPECIFICATIONS

Hydraulic Requirements and Functions			
Model #	Tamper Circuit	Rotation Circuit	Tamping Tools Circuit
DTT-4HD	32-33gpm@ 2300psi	10gpm@2000psi	10-15gpm@2000psi
Functions required	1 way Case drain	2 way medium pressure	2 way medium pressure
SHIPPING DIMENSIONS & WEIGHTS			
Height (in.)	Depth (in.)	Width (in.)	Weight w/ stand (lbs)



Dymax Tamper Stands
 Keep your tamper safe during transport
 and storage. Tie downs included.
 Stands sold separately

Materials and specifications subject to change without notice.



Dymax Inc. 402 Miller Drive PO Box 297 Wamego KS 66547 USA
 (p) 785-456-2081 (f) 785-456-8328 www.Dymaxattachments.com www.DymaxRail.com

Form No. 8160