

DYMAX WORK TOOLS

RAILWAY PULL CARTS

OVERVIEW

Dymax Railway Pull Carts and Trailers are ideal for mainline rail work and can be used on any rail line to transport work tools, ties and other on track materials.

Each Dymax Rail pull cart features air or hand brakes, a lighting package, steel decking with standard tie down locations, lifting points and recessed stake pockets on the outside. Available for specific gauge requirements such as narrow gauge, standard gauge or broad gauge.

All railway trailers feature solar powered lighting with direction sensing technology. The self contained lighting system is self charging, and removes any need to wire to the hi-rail grapple truck or other rail maintenance vehicle.

Dymax Rail Pull Carts and Trailers are offered as a standard 8 feet wide x 16 feet long work car, with a 20,000 lb to 60,000 lb capacity rating, depending on model. Custom trailers are available.

Dymax Rail Pull Carts feature heavy duty pintle connections as standard offering. Towbars feature a cast pintle eye welded into each end and are matched to the actual machine towing the trailer. Rail pull carts come with a 12 foot tow bar with storage rack.

Options include steel uprights for hauling ties, or Gondola side frames for increased hauling capacity of ballast or other scrap materials.



Model #	Description	Dimensions	GVWR	Brake Type	Weight lb	Weight kg
DX-RT-8x16x10T-RR	Rail Trailer / Pull Cart - Heavy Duty 8 x 16 x 20,000 lb capacity	Length: 192 in. Width: 96 in.	20,000 lb (10 ton capacity)	Hand Parking Brake or Air Brakes	4,400	1,995
DX-RT-8x16x20T-RR	Rail Trailer / Pull Cart - Heavy Duty 8 x 16 x 40,000 lb capacity	Length: 192 in. Width: 96 in.	40,000 lb (20 ton capacity)	Hand Parking Brake or Air Brakes	5,000	2,268
DX-RT-8x16x30T-RR	Rail Trailer / Pull Cart - Heavy Duty 8 x 16 x 60,000 lb capacity	Length: 192 in. Width: 96 in.	60,000 lb (30 ton capacity)	Hand Parking Brake or Air Brakes	7,500	3,402

All models feature 16in / 410mm diameter wheels and solar powered, red/white direction sensing lights. Optional removeable Gondola side frames for holding materials, or steel upright columns for scrap ties on all models.



DYMAX Rail
402 Miller Drive
Wamego, KS 66547 USA

Toll Free: 800.530.5407 (USA/CAN)
Office: +1.785.456.2081
Fax: +1.785.456.8328

www.DYMAXRAIL.com
sales@DYMAXRAIL.com